

Grade 1040 Bright Steel										
Typical Composition						Min.		Max.		
			Carbon			0.37%		0.44%		
			Manganese			0.60%		0.90%		
			Silicon			0.10%		0.35%		
			Phosphorus					0.04%		
			Sulphur					0.04%		
Mechanical Pr	operties (Approxim	nate M	1inimum)							
Tensile MPa (N/mm ²)					Elongation - %					
Cold Drawn TRD			& POL		Col	Cold Drawn		TRD & POL		
MM under 17	MM 17 to 38	MM 39 t	:0 63	MM to 260	MM under 17		MM 17 to 38	MM 39 to 63	MM to 260	
650	610	600		540	8		9	10	16	
Related Specifications										
	AS1443 - 1040									
		BS970 PART 1 1983 0801M 40								
		(EN8)								
SAI				SAE/AISI 1040						
GRADE 1B										
For further technical information, please contact our sales office.										
		Stocked Sizes			9.53mm - 101.6mm diameter					
		Bar Finish			Cold Drawn, Turned & Polished					
		Colour Code			Golden Tan (bar end).					

Interlloy believes the information provided is accurate and reliable. However no warranty of accuracy, completeness or reliability is given, nor will any responsibility be taken for errors or omissions.

Copyright © Interlloy Pty Ltd